

# RF POWER AMPLIFIERS MODEL 8000-064



**ETS-Lindgren's Model 8000-064 RF Power Amplifier** is a 15 W power amplifier, designed primarily for EMC applications that include IEC/EN 61000-4-3, up to 3 V/m requirements. Utilizing GaN technology, this RF amplifier provides higher linearity, rugged design and better efficiency performance versus silicon-based amplifiers.

The 8000-064 provides very low distortion and tolerance for 100% mismatch.

## MODEL 8000-064

- IEC/EN 61000-4-3, for 3 V/m
- High Reliability
- GaN Design
- Excellent Performance
- Efficiency Safety Interlock

## Technical Specifications

### Electrical

Frequency Range	600 MHz to 6 GHz
Nominal Output Power	15 W
Gain Variation	± 3 dB
Harmonics	-20 dBc Maximum
Output Impedance	50 Ω
Input VSWR	2:1 Maximum
AC Supply	100 to 240 VAC, Single Phase
Supply Frequency Range	50/60 Hz
Line Power	< 150VA

### Mechanical

RF Connectors	Type N (f)
Remote Interface	GPIB, LAN, Ethernet

### Physical

Dimensions	19 in, 3U Case, 500 mm (19.6 in) Deep
Weight	6.0 kg (13.2 lb)
Case Style (Standard)	Rack Mount with Rear Panel Connectors
Case Style (Optional)	Bench Mount, Front Panel Connectors