

RF POWER AMPLIFIERS MODEL 8100-085



ETS-Lindgren's Model 8100-085 RF Power Amplifier is a 60W power amplifier, designed primarily for EMC applications that include MIL-STD 461 RS 103 requirements. This solid state RF amplifier provides higher linearity, rugged design and better efficiency performance versus silicon-based amplifiers.

The 8100-085 provides very low distortion and tolerance for 100% mismatch.

MODEL 8100-085

- MIL-STD 461 RS 103
- High Reliability
- Excellent Performance and Efficiency
- Safety Interlock

Technical Specifications

Electrical	
Frequency Range	4 GHz to 8 GHz
Nominal Output Power	60 W
Gain Variation	± 3 dB
Harmonics	-20 dBc Maximum
Output Impedance	50 Ω
Input VSWR	2:1 Maximum
AC Supply	100 to 240 VAC, 10% Single Phase
Supply Frequency Range	50/60 Hz
Line Power	< 900 VA
Mechanical	
Remote Interface	GPIB, Ethernet, USB
RF Connectors	Type N (f)
Physical	
Dimensions	19 in, 3U Case, 630 mm (24.8 in) Deep
Weight	22.0 kg (48 lb)
Case Style (Standard)	Rack Mount with Rear Panel Connectors
Case Style (Optional)	Bench Mount, Front Panel Connectors